

Lubricants for industry.

Blamedol T-15

Technical-grade white medical lubricant



Use

- Technical-grade white medical lubricant for use in all production processes requiring a non-additive medical white lubricant.
- In general, this product is recommended for use where low toxicity is required due to indirect or accidental contact with food and where compliance with pharmacopoeia specifications is not required.
- Recommended for use in the food industry, animal feed industry, textiles, insecticides, rubber, cork specialties, plastics, precision instruments, etc.

Benefits

- Stability against light and heat.
- High viscosity index.
- Harmless when handling.
- Concentrations of utilization according to FDA recommendations.
- Compatible with mineral oil.
- Recommended for use in applications where accidental contact with food may occur or be present.

Specifications

- NSF Nonfood Compounds Registration (H1)
- FDA 21 CFR 178.3620 (b)

Physical and chemical properties

Parameter	Units	Method	Blamedol T-15
ISO Grade	-	-	15
Density at 15 °C	kg/l	ASTM D-1298	15
V/A flash point, min.	°C	ASTM D-92	0.85
Pour point, max.	°C	ASTM D-97	180
Viscosity at 40°C	cSt	ASTM D-445	-9
Ultra-violet absorption	-	21 CFR 178.3620 (b)	15

Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.