

LUBRICANTS FOR INDUSTRIAL USE

CEPSA EXTOIL

DESCRIPTION

Lubricating oils formulated with highly refined paraffin bases.

PRODUCT APPLICATION

- Plasticisers for the rubber industry.
- Especially recommended for calendering, extrusion and moulding processes, and for use as extenders.

PRODUCT PERFORMANCE

- High molecular weight and high aniline point: It has good rebound resilience in rubber mixtures, while enhancing their properties at low temperatures.
- Limited polymer compatibility, no staining and high colour stability: Recommended in the manufacturing of nitrile rubbers (NRB) and styrene butadiene rubbers (SBR) when used in appropriate proportions.

TYPICAL CHARACTERISTICS

CHARACTERISTIC	ASTM STANDARD	CEPSA EXTOIL 30	CEPSA EXTOIL 90	CEPSA EXTOIL 250	CEPSA EXTOIL 500
Density 15°C, kg/l	D-1298	0.875	0.890	0.900	0.908
Flammability V/A, °C, min.	D-92	210	260	260	282
Freezing point, °C	D-97	-12	-6	-6	-6
Viscosity at 40°C, cSt	D-445	32	113	265	492
Viscosity index	D-2270	100	95	95	95

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.