

## LUBRICANTS FOR INDUSTRIAL USE

# CEPSA TERMOCLEAN

### DESCRIPTION

Synthetic cleaning fluid for cleaning hydraulic and thermal circuits.

#### PRODUCT APPLICATIONS

- The product is used diluted in the circuit to be cleaned.
- The product CEPSA TERMOCLEAN must be used at a minimum rate of 5% (or more, depending on how dirty the circuit is), mixed with the oil in circulation, and at the normal operating temperature (between 50-60 °C for hydraulic circuits and 270 °C in thermal circuits), for 48 hours before the oil change.
- The circuit must be completely removed and the filters changed before filling the circuit with the new oil.
- It can be used preventively in circuits that are susceptible to accumulating dirt, thereby achieving better control over the degree of circuit cleaning.
- Avoid contamination with water.

#### PRODUCT PERFORMANCE

- It has a high detergency and dispersancy level, ensuring effective circuit cleaning.
- Excellent thermal stability.
- Miscible with all hydraulic fluids and mineral base thermal fluids.

### TYPICAL CHARACTERISTICS

CHARACTERISTICS	UNITS	METHOD	CEPSA TERMOCLEAN
Density at 15 °C	Kg/L	ASTM D-4052	0,909
Flash Point, COC	°C	ASTM D-92	203
Viscosity at 40 °C	cSt	ASTM D-445	25,6
Viscosidad a 100°C	cSt	ASTM D-445	4,62
Aniline Point	°C	ASTM D-611	59,4

### HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.