

Lubricants for industry.

Circulating R&O 100



High-quality, universal use lubricant for industrial circulation and bearing systems, type "R&O" (protection against rust and oxidation).

Use

- Product formulated with specially selected paraffinic base oils and additivation to provide the product with the properties required for its multiple applications.
- Suitable for use in all types of circulation lubrication systems without major requirements, as well as in reducers, speed variators (that do not require a specific oil), and bearings under normal load and temperature conditions, and in reciprocating compressors under normal operating conditions (non-severe).
- Also suitable for steam, hydraulic and gas turbines operating at low temperatures and in hydraulic circuits where special anti-wear properties are not required.

Benefits

- Due to its anti-rust and anti-corrosion qualities, it has a wide range of applications, reducing the stock of oil in the plant.
- It has adequate resistance to oxidation, and thermal and chemical stability.
- It avoids premature deterioration of gaskets and elastomers.
- Fluidity and high lubricity in boundary lubrication conditions.
- Good demulsibility (water separation) and resistance to foaming.
- Long service life with resulting savings in component lubrication.

Specifications

- DIN 51524 Part 1(HL)
- DIN 51515 Part 1(L-TD)
- DIN 51517 (CL)
- ISO 6743-2 FC

Physical and chemical properties

Parameter	Units	Method	Circulating R&O 100
ISO Grade	-	-	100
Density at 15 °C	Kg/l	ASTM D-4052	0.889
Flash Point, COC	°C	ASTM D-92	264
Pour Point	°C	ASTM D-5950	-18
Viscosity at 40°C	cSt	ASTM D-445	95
Viscosity at 100°C	cSt	ASTM D-445	10.9
Viscosity index	-	ASTM D-2270	98
Rust prevention (Proc. A)	-	ASTM D-665	Pass

Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.