

Lubricants for industry.



## Blamedol 15 AF

Medical white food-grade lubricant.

### Use

- Formulated with fully saturated hydrocarbons, free from sulfonates, and in compliance with purity requirements required by the ultraviolet absorption test.
- Specially formulated for use in processing of feeds and other animal industry-related materials.

### Benefits

- Registered in NSF for use in applications that require a toxic free mineral oil.
- This product has the name of raw material for animal feed designation found under registration number ESP-28000512 in accordance with Regulation (EC) 183/2005.

### Specifications

- NSF Nonfood Compounds Registration (H1)
- FDA 21 CFR 172.878 / 178.3620 (a)
- PHARMACOPOEIAS USP (American), EUP (Europe), Royal Pharmacopoeia Española (RFE), CODEX

### Physical and chemical properties

Parameter	Units	Method	Blamedol 15 AF
ISO Grade	-	-	15
Saybolt color, typical	-	ASTM D-156	+ 30
Density 15°C	Kg/l	ASTM D-1298	0.853
Flash Point, min.	°C	ASTM D-92	170
Pour point, max.	°C	ASTM D-97	-6
Viscosity at 100°C, max.	cSt	ASTM D-445	5.0
Viscosity at 40°C	cSt	ASTM D-445	16.5
Acidity index	mg KOH/g	ASTM D-664	0
Scent and flavor	-	-	Exempt
Non-sulfonated residue	-	ASTM D-483	100
Carbonizable Substances.	-	Pharmacopoeias	Pass
Ultra-violet absorption	-	Pharmacopoeias	Pass

### Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.