

Lubricants for industry.



## Hydrowork EP 10W-20

Multi-grade hydraulic fluid with Extrema-Pressure properties developed for use in mobile equipment.

### Use

- Moeve Hydrowork EP 10W-20 is formulated with highly refined bases and specific additives, which provide the properties required for Extreme Pressure and Antiwear hydraulic fluids for Mobile Equipment.
- Specifically recommended for hydraulic systems of Public Works and Mining in harsh conditions of use.

### Benefits

- Excellent Extreme-Pressure and anti-wear capacity.
- Excellent resistance to foaming tendency and good release of occluded air.
- High protection against corrosion and rust.
- Highly resistant to oxidation.
- High filterability.

### Specifications

• DIN 51524 Part 2 HLP	• ISO 11158 HM;
• ISO 6743-4 HM	• EATON Brochure 03-401-2012
• ISO 11158 HM	

### Physical and chemical properties

Parameter	Units	Method	Hydrowork EP 10W-20
<b>ISO Grade</b>	-	-	<b>46</b>
Viscosity at 40 °C	cSt	ASTM D-445	43.1
Viscosity at 100° C	cSt	ASTM D-445	7.1
Viscosity index	-	ASTM D-2270	125
Density 15 °C	kg/l	ASTM D-4052	0.878
Flash point COC	°C	ASTM D-92	220
Pour point	°C	ASTM D-97	-27

### Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.