

Lubricants for industry.



## Motosierras

Lubricant for the lubrication of chainsaw chains.

### › Use

- Lubricant formulated with highly refined paraffinic base oils and a viscosity that provides the product with high adhesion to the surface to be lubricated.

### › Benefits

- High viscosity.
- Decrease in oil losses.
- High surface adhesion.
- Decrease in oil consumption.
- High oxidation resistance.
- Prevents metallic wear.

### › Specifications

- DIN 51501 L-AN
- ISO 6743/1 L-AN
- ISO 6743/4 HL

### › Physical and chemical properties

Characteristic	Units	Method	Chainsaws
Density 15 °C	Kg/l	ASTM D-4052	0.884
Flash point	°C	ASTM D-92	240
Pour point	°C	ASTM D-5950	-30
Viscosity at 100 °C	cSt	ASTM D-445	18
Viscosity at 40 °C	cSt	ASTM D-445	150
Viscosity index	-	ASTM D-2270	129

### › Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.