

Lubricants for industry.

Motosierras



Lubricant for the lubrication of chainsaw chains.

> Use

- Lubricant formulated with highly refined paraffinic base oils and a viscosity that provides the product with high adhesion to the surface to be lubricated.

> Benefits

- High viscosity.
- Decrease in oil losses.
- High surface adhesion.
- Decrease in oil consumption.
- High oxidation resistance.
- Prevents metallic wear.

> Specifications

- DIN 51501 L-AN
- ISO 6743/1 L-AN
- ISO 6743/4 HL

> Physical and chemical properties

Characteristic	Units	Method	Chainsaws
Density 15 °C	Kg/l	ASTM D-4052	0.884
Flash point	°C	ASTM D-92	240
Pour point	°C	ASTM D-5950	-30
Viscosity at 100 °C	cSt	ASTM D-445	18
Viscosity at 40 °C	cSt	ASTM D-445	150
Viscosity index	-	ASTM D-2270	129

> Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.