

Lubricants for industry.



Hydrowork EP 10W-20

Multi-grade hydraulic fluid with Extrema-Pressure properties developed for use in mobile equipment.

› Use

- Moeve Hydrowork EP 10W-20 is formulated with highly refined bases and specific additives, which provide the properties required for Extreme Pressure and Antiwear hydraulic fluids for Mobile Equipment.
- Specifically recommended for hydraulic systems of Public Works and Mining in harsh conditions of use.

› Benefits

- Excellent Extreme-Pression and anti-wear capacity.
- Excellent resistance to foaming tendency and good release of occluded air.
- High protection against corrosion and rust.
- Highly resistant to oxidation.
- High filterability.

› Specifications

- DIN 51524 Part 2 HLP
- ISO 6743-4 HM
- ISO 11158 HM
- ISO 11158 HM;
- EATON Brochure 03-401-2012

› Physical and chemical properties

Parameter	Units	Method	Hydrowork EP 10W-20
ISO Grade	-	-	46
Viscosity at 40 °C	cSt	ASTM D-445	43.1
Viscosity at 100° C	cSt	ASTM D-445	7.1
Viscosity index	-	ASTM D-2270	125
Density 15 °C	kg/l	ASTM D-4052	0.878
Flash point COC	°C	ASTM D-92	220
Pour point	°C	ASTM D-97	-27

› Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.