

# ERTOIL LICENA HS/95

## DESCRIPTION



Safety hydraulic fluid, oil-water emulsion type (HFA).

Water soluble oil, with lubricant, anti-foam properties, which is resistant to both fire and bacteria.

### Applications

- Application in hydraulic systems for presses in the wood industry where a fluid of these characteristics is required.
- Also applications in mining, for HFA systems.

### Performance

- Exceptional bacterial resistance.
- Good anti-corrosion and anti-rust powers .
- Does not form deposits.
- Does not attack seals or paint.

## TYPICAL CHARACTERISTICS

CHARACTERISTICS	NORMA	ERTOIL LICENA HS/95	
<b>1. CONCENTRATE</b>			
Aspect	Visual	Transparent Red-brown	
Stability in storage 7 days at +24°C 24 hours at + 40°C	Visual	Stable Stable	
<b>2. EMULSIÓN, 5% IN DISTILLED WATER</b>		<b>of TH 20</b>	<b>DISTILLED</b>
Aspect	Visual	Transparent Milky-white	
Stability in storage 7 days at +24°C 24 hours at + 40°C	Visual	Stable Stable	Stable Stable
PH	DIN 51369	9.1	9.0
Foam	CNOMO 655212	Complies	Complies
Herbert Test	DIN 51360/1	0/0-0	0/0-0
Filter Paper Test	DIN 51360/2	0	0
<b>3. EMULSION AT 3% IN DISTILLED WATER</b>			
Herbert Test	DIN 51360/1	0/0-0	
Filter Paper Test	DIN 51360/2	1	

## HEALTH & SAFETY and ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.