

TRANSMISSIONS



MOTOR VEHICLE LUBRICANTS

CEPSA ATF CVT

DESCRIPTION

High-quality 100% synthetic oil, developed to meet the requirements of the new continuous variable transmissions (CVT). The technology used in this product provides optimal properties for protection from the wear caused by metal-metal friction that occurs between the belt and the pulley.

PRODUCT APPLICATIONS

- Formulated to meet the requirements of CVT transmissions.

PRODUCT PERFORMANCE

- Optimal viscosity for this type of transmissions.
- Exceptional cleaning of the transmission system.
- Protection from the wear produced by the friction that occurs within the transmission.

SPECIFICATIONS

Optimal product for use in the CVT transmissions of the main manufacturers:

- FORD
- HONDA
- TOYOTA
- NISSAN
- MITSUBISHI
- HYUNDAI
- SUZUKI
- MERCEDES BENZ

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA ATF CVT
Density at 15°C	Kg/l	D-4052	0.932
Flash point V/A	°C	D-92	>200
Pour point	°C	D-97	-48
Viscosity at 100°C	cSt	D-445	7.19
Viscosity at 40°C	cSt	D-445	33.69
Viscosity Index	-	D-2270	185
Brookfield viscosity -40°C	cP	D-2983	10000

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.