

TRANSMISSIONS



MOTOR VEHICLE LUBRICANTS

CEPSA ATF DCT

DESCRIPTION

High-quality 100% synthetic oil, developed to meet the requirements of the new double clutch transmissions (DCT). The product possesses optimal characteristics for protection against wear due to friction and minimization of the vibration that takes place in this type of transmission.

PRODUCT APPLICATIONS

- Formulated to meet the requirements of DCT transmissions.

PRODUCT PERFORMANCE

- Optimal protection of transmissions in a wide temperature range.
- Exceptional cleaning of the transmission system.
- Protection of the transmission against wear and corrosion.

SPECIFICATIONS

Optimal product for use in the DCT transmissions of the main manufacturers:

- FORD
- VOLKSWAGEN
- CITRÖEN
- PEUGEOT
- MITSUBISHI
- PORSCHE
- VOLVO
- MERCEDES BENZ

TYPICAL CHARACTERISTICS

| CHARACTERISTIC | UNITS | METHOD | CEPSA ATF CVT |
|----------------------------|-------|--------|---------------|
| Density at 15°C | Kg/l | D-4052 | 0.856 |
| Flash point V/A | °C | D-92 | 194 |
| Pour point | °C | D-97 | -54 |
| Viscosity at 100°C | cSt | D-445 | 6.9 |
| Viscosity at 40°C | cSt | D-445 | 34 |
| Viscosity Index | - | D-2270 | 168 |
| Brookfield viscosity -40°C | cP | D-2983 | 12400 |

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.