

## LUBRICANT OILS FOR AGRICULTURAL MACHINERY

### CEPSA AURIGA TE 85

#### DESCRIPTION

UTTO oil formulated to comply with the requirements of FORD M2C 86B specifications for hydraulic systems and brakes submerged in an oil bath. Complies with MASSEY FERGUSON MF 1135 specifications.

#### PRODUCT APPLICATIONS

- High oxidation stability.
- Good antiwear and Extreme Pressure properties.
- Superb protection against corrosion and rust.
- High resistance to foam formation.
- Superb fluidity at low temperatures.
- Compatible with sealing materials.

#### PRODUCT PERFORMANCE

- Reduces the formation of sludge, lacquers and varnishes.
- High load capacity.
- Perfect lubrication at all operating speeds.
- Immediate oil circulation at start-up.
- No more vibration and screeching from brakes submerged in an oil bath.

#### SPECIFICATIONS

- API GL-4
- MF M1135
- FORD M2C 86 B

#### TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA AURIGA TE 85
Density at 15°C	Kg/l	D-4052	0.892
Flash point COC	°C	D-92	245
Pour point	°C	D-97	-33
Viscosity at 100°C	cSt	D-445	10.9
Viscosity at 40°C	cSt	D-445	84.3
Viscosity index		D-2270	116

#### HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.