

Products for car maintenance.

AdBlue



A 32.5% by weight aqueous urea solution, complementary to fuel, suitable for engines equipped with selective catalytic reduction (SCR) technology. Avoid storing at temperatures above 25°C and protect from sunlight.

› Use

- MOEVE ADBLUE is a nitrogen oxide (NOx) reducer, specially formulated for diesel vehicles equipped with Selective Catalytic Reduction (SCR) systems.
- It must be used exclusively in the tank intended for Adblue. It must not be mixed with fuels or oils.

› Benefits

- SCR technology reduces the NOx emissions generated during combustion through a catalytic converter, transforming them into nitrogen and steam, harmless components found in the atmosphere.
- MOEVE ADBLUE has been developed to meet the emission requirements established in the Euro 4, Euro 5, and Euro 6 regulations.
- The product retains its properties for a period of up to 18 months from the date of manufacture, provided it is kept sealed in its original container, protected from sunlight, and at a temperature below 25°C.

› Quality standards

- ISO 22241 (parts 1-4)

› Physical and chemical properties

Characteristic	Units	AdBlue
Appearance	-	Clear, colorless liquid
Density at 20°C	kg/l	1.090
Viscosity at 25°C	mPa s	1.4
Urea content	%	31.8-33.2
Crystallization Point	°C	-11.5
Refraction index (20°C)	-	1.3817 – 1.3840

› Health & safety and environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.