

MOTOR VEHICLE LUBRICANT OILS. PASSENGER CARS

CEPSA GENUINE 10W40 MAX

DESCRIPTION

A lubricant formulated with synthetic technology and an additivation that provides the engine with excellent protection, even with the most rigorous use. Developed to meet the requirements of direct injection petrol and diesel engines, it is suitable for dual CNG/LPG engines, both in light vehicles and off-road, 4x4 and light diesel vehicles (vans and light trucks).

PRODUCT APPLICATIONS

- For use in modern high-performance and luxury vehicle engines: saloon and sports cars and, in general, any with very high-powered engines.
- For designs with the latest technologies: turbocharged, direct injection, multi-valve, HDI etc.
- For all types of weather and driving conditions, especially in severe service conditions.
- Compatible with catalytic exhaust systems, except particulate filters.

PRODUCT USES

- The ACEA A3/B4 level ensures high protection against wear, especially in direct injection and dual camshaft engines.
- API SN certification ensures greater protection against the formation of deposits on pistons at high temperatures, reduces the formation of sludge and has greater compatibility with non-metallic engine components, preventing premature degradation.
- It facilitates cold starting and contributes to fuel savings compared to higher viscosity oils.
- Low volatility and low oil consumption on long journeys.

SPECIFICATIONS

- ACEA A3/B4
- API SN
- MB 229.1
- RN 0700
- VW 501.01/505.00



TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA GENUINE 10W40 MAX
SAE Grade	-	-	10W40
Density at 15°C	g/ml	ASTM D 4052	0.872
Viscosity at 100°C	cSt	ASTM D 445	14.4
Viscosity at 40°C	cSt	ASTM D 445	97.9
Viscosity index	-	ASTM D 2270	151
CCS viscosity at -25°C	cP	ASTM D 5293	6618
Freezing point	°C	ASTM D 5949	-39
Flash point, V/A	°C	ASTM D 92	224
Base number, TBN	mg KOH/g	ASTM D 2896	10.7
Sulphated ash	% (m/m)	ASTM D 874	1.2
HTHS viscosity at 150°C	cP	ASTM D 4683	3.9

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.