

AUTOMOTIVE LUBRICANTS. PASSENGER CARS

CEPSA GENUINE 15W40

DESCRIPTION

Multi-grade oil, specially designed to exceed the API SL/CF specification, covering the levels of demand of gasoline and diesel engines for passenger cars of any range: SUVs, sedans, minivans, etc.

PRODUCT APPLICATIONS

- Intended for the engines of the main manufacturers, it is suitable for all models of cars, vans and light diesel.
- For turbocharged gasoline engines, direct injection, common-rail, intercooler, etc. and traditional diesel technologies (indirect injection).
- For all types of weather and driving.

PRODUCT PERFORMANCE

- Suitable for all seasons, it guarantees good lubrication of the entire engine at start-up, even at low temperatures.
- It reduces friction between the metal parts of the engine, preventing possible wear or seizure.
- High detergent/dispersant level, which prevents the accumulation of sludge and dirt in the engine, keeping it clean and protected.

TYPICAL CHARACTERISTICS

- API SL/CF

SPECIFICATIONS

CHARACTERISTIC	UNITS	METHOD	GENUINE 15W40
SAE Grade	-	-	15W-40
Density 15°C	g/ml	ASTM D 4052	0.884
Viscosity at 100°C	cSt	ASTM D 445	14.4
Viscosity at 40°C	cSt	ASTM D 445	107
Viscosity Index	-	ASTM D 2270	137
CCS Viscosity at -20°C	cP	ASTM D 5293	5616
Pour Point	°C	ASTM D 5950	-33
Flash Point, COC	°C	ASTM D 92	228
Base number, TBN	mg KOH/g	ASTM D 2896	7.6
Sulfated ash	% (m/m)	ASTM D 874	1.01
HTHS Viscosity at 150°C	cP	ASTM D 4683	4.15

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.