

MARINE LUBRICANTS

CEPSA CICONIA 30

DESCRIPTION

CEPSA CICONIA 30 oil has been developed to lubricate the crankcase of slow two-stroke marine diesel engines.

The product is formulated with highly refined base oils and has good anti-corrosion and anti-foaming properties. Its characteristics include a slight alkalinity, which helps neutralise acidic products resulting from combustion, which can enter the engine's crankcase cavity. It has a high degree of detergency and excellent oxidation stability, which ensures the cleanliness of the engine.

PRODUCT PERFORMANCE

- Excellent protection from wear and tear.
- Excellent detergent/dispersant properties, ensuring that the crankcase is cleaned.
- Protects all engine parts from corrosion.
- Prevents foams from forming.
- It has optimum characteristics to help clean the oil purifiers.

SPECIFICATIONS

- MAN B&W Diesel
- WÄRTSILÄ

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	ASTM STANDARD	CEPSA CICONIA 30
SAE GRADE		---	30
Density at 15°C	kg/l	D-4052	0.894
Flash point V/A	°C	D-92	>220
Freezing point,	°C	D-97	-6
Viscosity at 40°C	cSt	D-445	110
Viscosity at 100°C	cSt	D-445	11.95
Viscosity index	-	D-2270	96
Base number, (min)	mg KOH/g	D-2896	5

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product in accordance with the applicable legislation.