MOTO



MOTORCYCLE LUBRICANTS

CEPSA MOTO 2T UNIVERSAL ත්ර

DESCRIPTION

A mineral lubricant oil for all types of moderately powered two-stroke engines under normal conditions of use. Recommended for gardening and DIY tools and for low-capacity motorcycles and mopeds.

PRODUCT APPLICATIONS

• Suitable for use when the power/size ratio of the motor is crucial and, generally, for small motors that do not require emissions control.

• In gardening and DIY tools with moderate demands in terms of operation and performance: lawnmowers, chainsaws, electrical generators, irrigation pumps, etc.

• Compatible with all types of petrol, it should be used as a 2% premix or at the dose recommended by the manufacturer.

PRODUCT PERFORMANCE

• Its viscosity and special additivation allow rapid greasing of all parts of the engine, providing a higher starting torque and better lubrication than other conventional oils.

• Provides optimal protection and engine cleaning, with no seizure, due to its high detergent power.

• Its good dispersant capacity prevents deposits from forming in the pistons and ports, thus extending the lifespan of the spark plugs without fouling.

SPECIFICATIONS

JASO FB

ISO L-EGB

• API TC

TYPICAL CHARACTERISTICS

CHARACTERISTIC	UNITS	METHOD	CEPSA MOTO 2T UNIVERSAL
Density at 15°C	g/ml	ASTM D4052	0.883
P/M Flash Point	٥C	ASTM D93	94
Pour Point	٥C	ASTM D5950	-21
Viscosity at 100°C	cSt	ASTM D445	8.79
Viscosity Index	-	ASTM D2270	116
Total Base Number (TBN)	mg KOH/g	ASTM D2896	1
Color	-	ASTM D1500	Red

HEALTH & SAFETY AND ENVIRONMENT

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The values for typical specifications shown in the table are average values provided for illustrative purposes and do not constitute a guarantee. These values are subject to modification without prior warning.